

Summary

This section contains the formulas, rules, and principles, and the rate schedules and calculation procedures for determining the assessed value of oil and gas well resource production equipment, and buildings located at an oil or gas well site.

Description

Resource production equipment includes the fixtures, machinery and other appliances by which petroleum oil or gas is produced to the surface, stored, transported from a well site or a battery or gas handling site, or is compressed.

Resource production equipment does not include the fixtures, machinery and other appliances by which petroleum oil or gas is stored at a battery site, or is compressed where the gas is, for the most part, a by-product of petroleum oil production.

Oil or Gas Well Site

The area of land on or under which is located the resource production equipment used to raise or pump the oil or gas to the surface, the resource production equipment used to inject air, water, steam or gas to enhance the production of a well, or the resource production equipment at a water source well, that was operated for 30 or more days in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

The resource production equipment located at an oil well site includes the pumping equipment, wellhead assembly, tubing and rods, and well accessories.

The resource production equipment located at a gas well site includes the wellhead assembly, tubing, chemical equipment, water handling equipment, and metering equipment.

The resource production equipment used to inject air, water, steam or gas to enhance the production of a well, and the resource production equipment at a water source well, includes the pumping equipment, wellhead assembly, tubing and rods, metering equipment, control valves, manifold, and well accessories.

New Well Site

An oil or gas well site that was drilled in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

Swabber Well Site

An oil or gas well site where on July 1 of the preceding year to which the assessment roll relates, the resource production equipment used in the preceding year has been removed from the site and has not been replaced with any other on-site resource production equipment.

Shut-In Well Site

The area of land on or under which is located the resource production equipment used to raise or pump the oil or gas to the surface, the resource production equipment used to inject air, water, steam or gas to enhance the production of a well, or the resource production equipment at a water source well, that was operated for less than 30 days in the 12 month period ending September 1 of the preceding year to which the assessment roll relates.

Observation Well Site

The area of land on or under which is located the resource production equipment used to monitor an oil or gas well to enhance the production of the well.



Resource Production Equipment Subject: General Rules

Gas Storage Well Site

The area of land on or under which is located the resource production equipment used to inject gas into a gas cavern or sub surface formation and to pump gas from a gas cavern or subsurface formation.

Flow Line

A flow line is a line of pipe used to transport oil or gas from a well site to a battery or gas handling site.

Replacement Cost New

The replacement cost new of oil and gas well resource production equipment and buildings located at an oil or gas well site, or a new well site shall be determined by the standard unit method.

The replacement cost new of oil and gas well resource production equipment located at a swabber well site or shut-in well site shall be limited to the wellhead assembly which shall be determined in accordance with the wellhead assembly specifications in Chapter 4 - Resource Production Equipment, Section 4.1.3 - Oil and Gas Well Resource Production Equipment, Well Classification.

The replacement cost new of oil and gas well resource production equipment located at an observation well site or gas storage well site, and the replacement cost new of flow lines shall be determined by the unit-in-place method.

The trended original cost method for determining replacement cost new shall be used where the replacement cost new of specific oil or gas well resource production equipment cannot be determined by the standard unit method or the unit-in-place method.

The trended original cost shall include all direct and indirect costs. Direct costs include materials, labour, supervision, equipment rentals, and utilities. Indirect costs include architectural and engineering fees, building permits, title and legal fees, insurance, interest and fees on construction loans, taxes incurred during construction, advertising and sales expenses, and overhead and profit. Trended original costs shall be determined FOB the well site as of January 1, 2015.

Standard Unit Method

The replacement cost new shall be determined as follows:

- 1. Determine the classification of the well.
- 2. Determine the resource production equipment needed to operate a substitute well. The substitute well must perform the same function as the well being valued.
- 3. Calculate the replacement cost new of the resource production equipment located at the well by summing the replacement cost of the substitute resource production equipment.

Unit-In-Place Method

The replacement cost new shall be determined as follows:

- 1. Determine the type of resource production equipment using the rating guide.
- 2. Determine the features requiring a unit-in-place lump sum or percentage adjustment.
- 3. Calculate the replacement cost new of the resource production equipment by adjustment of the base rate by the unit-in-place adjustments.



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment Subject: General Rules

Trended Original Cost Method

The replacement cost new shall be determined as follows:

- 1. Determine the original construction cost of all the resource production equipment at the facility.
- 2. Determine the direct and indirect costs requiring an adjustment.
- 3. Determine the direct and indirect cost factor for oil and gas resource production equipment required to adjust construction costs to January 1, 2015.
- 4. Calculate the construction cost of all the resource production equipment at the facility by adjusting the original construction cost for any direct or indirect costs requiring adjustment and multiplying the adjusted original construction cost by the comparative cost index.
- 5. Determine replacement cost of resource production equipment that can be separately identified and rated by the unit-in-place method.
- 6. Calculate the replacement cost of the resource production equipment that can not be separately identified by subtracting the replacement cost of separately identified components from the construction cost of all the resource production equipment at the facility.

Physical Deterioration

The amount of physical deterioration for oil and gas well resource production equipment and buildings shall be determined using the lifetime depreciation method. No allowance shall be made for functional and economic obsolescence, except as may be accounted for in the downtime allowance or the production adjustment factor.

Lifetime Depreciation Method

The amount of physical deterioration shall be 40 percent. When calculating replacement cost new less depreciation no additional allowance shall be made for physical deterioration except as may be accounted for in the production adjustment factor.

Downtime Allowance

The downtime allowance for oil and gas well resource production equipment shall be determined by the schedule of rates method.

The downtime allowance shall account for the loss in value due to under-utilization of the resource production equipment. This includes any loss in value due to differences in replacement cost and differences in the amount of depreciation, that have not been taken into account using the procedures in this manual.

Schedule of Rates Method

The downtime allowance shall be 10 percent. When calculating replacement cost new less depreciation and downtime, no additional allowance shall be made for downtime except as may be accounted for in the production adjustment factor.

Production Adjustment Factor

The production adjustment factor for oil and gas well resource production equipment and buildings located at an oil or gas well site, and flow lines shall be determined by the schedule of rates method.

The production adjustment factor shall account for the loss in value due to under-utilization of the resource production equipment or buildings. This includes any loss in value due to differences in replacement cost and differences in the amount of depreciation, that have not been taken into account using the procedures in this manual.



A production adjustment factor shall not be applied to the oil and gas well resource production equipment located at a new well site, swabber well site, shut-in well site, observation well site, or gas storage well site.

Schedule of Rates Method

The production adjustment factor shall be 0.75 for qualified resource production equipment, buildings, structures and flow lines.



Resource Production Equipment Subject: General Rules

Section:

Qualifying Production Level

The production adjustment factor shall be applied to resource production equipment, buildings, structures and flow lines. The factor shall be a three year average of production from a 36 month period ending July 1 of the preceding year to which the roll relates.

The average production of the well shall be determined as follows:

- 1. Determine the volume of oil or gas produced by the well during the 12 month period of July 1 to June 30 for each of the three years.
- 2. Determine the number of days the well was operated during the 12 month period of July 1 to June 30 for each of the three years.
- 3. Calculate the production of the well for each year by dividing the volume of oil or gas produced by the well for the year by the number of days the well was operated during the year.
- 4. Calculate the average production of the well by summing the production of the well for the three years and dividing by three.

Oil Wells

		Qualifying Production Level		
Well Area (Abbreviation)	Crude Type	barrels/day	M³/day	
Warhum (WE)	Light	1.78	0.282	
weyburn (wE)	Medium	1.79	0.284	
	Light	1.24	0.197	
Swift Current (SC)	Medium	1.68	0.267	
	Heavy	3.49	0.555	
Kindomlay (KD)	Light	1.24	0.197	
Kindersley (KD)	Heavy	3.49	0.555	
North Battleford - South (NB-S)	Heavy	3.49	0.555	
North Battleford - North (NB-N)	Heavy	3.49	0.555	

Gas Wells

Well Area (Akhuariatian)	Qualifying Production Level		
wen Area (Abbreviauon)	cu.ft./day	M ³ /day	
Weyburn (WE)	19,710	558.10	
Swift Current (SC)	15,023	425.40	
Kindersley (KD)	17,026	482.12	
North Battleford - South (NB-S)	19,710	558.10	
North Battleford - North (NB-N)	19,710	558.10	



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment Subje

Subject: General Rules

Calculation Procedure

Resource Production Equipment at an Oil or Gas Well Site

Description	Document No.	Page No.
Standard Unit Resource Production Equipment [a), b), c)]		
a) Determine Well Characteristics		
a ₁ . Well Area	4.1.3	1
a ₂ . Well Type	4.1.3	1
a ₃ . Crude Type	4.1.3	1
a ₄ . Horizontal Completion	4.1.3	2
a ₅ . Depth	4.1.3	2
a ₆ . Rated Volume	4.1.3	2
a7. Facility Type	4.1.3	2
a ₈ . Days Operated	4.1.3	2
b) Determine Substitute Well Features	4.1.3	3-18
c) Base Rate = $(c_1 + c_2 + c_3 \dots + c_9)$		
c1. Pumping Equipment Rate	4.1.5	1-6
c ₂ . Well head Assembly Rate	4.1.4	1
c ₃ . Tubing and Rods Rate	4.1.7	1
c4. Chemical Equipment Rate	4.1.18	1
c ₅ . Water Handling Equipment Rate		
$c_5 = (c_{5.1} + c_{5.2})$		
c _{5.1} Separator Rate	4.1.8	1-5
c _{5.2} Scraper Traps Rate	4.1.27	1
c ₆ . Metering Equipment Rate	4.1.15	1-4
c7. Control Valves Rate	4.1.16	1-3
c ₈ . Manifold Rate	4.1.26	1
c9. Flow Line Rectifier Rate	4.1.20	1
d) Unit-in-Place Resource Production Equipment	4.1.1	2-3
e) Trended Original Cost Resource Production Equipment	4.1.1	2-3
f) Replacement Cost New = $(c + d + e)$		
g) RCN less Physical Deterioration and Downtime		
Allowance = $f x (1 - (g_1 + g_2))$		
g ₁ . Physical Deterioration	4.1.1	4
g ₂ . Downtime Allowance	4.1.1	4
h) Production Adjustment Factor	4.1.1	3-5
i) Assessed Value = $(g x h)$		

The calculation procedure for oil and gas well buildings on an oil or gas well site is found on Document 3.1.3, Page 1.



Subject: **Comparative Cost Factor**

Description

The comparative cost factors are used to determine the replacement cost of oil and gas well resource production equipment valued by the trended original cost method.

Section:

Application

The trended original cost method shall be used when the individual components of resource production equipment cannot be determined or estimated.

The trended original cost method shall not be used to determine the replacement cost of resource production and equipment located at an oil or gas well site, or to determine the replacement cost of resource production equipment that can be separately identified and rated.

Comparative Cost Factor

The comparative cost factor shall be used to calculate the replacement cost new of resource production equipment as of January 1, 2015.

Factors

Year	Comparative Cost Factor	Portions of this section at
1940 and older		viewing due to licensing
1941		Swift. Therefore the facto
1942		intentionally left blank.
1943		,
1944		This information is availa
1945		contacting:
1946		
1947		Technical Standards
1948		Saskatchewan Assess
1949		Ager
1950		200-2201-
1951		Regina, Saskatch
1952		\mathbf{D}
1953		Toll Eros: 1 800.64
1954		Fax: (306)
1955		1 ax. (500)
1956		Email: info reque
1957		Email: moneque
1958		Web Site: http://w
1959		web ble. <u>mp.//w</u>
1960		
1961		
1962		
1963		
1964		
1965		
1966		
1967		
1968		
1969		
1970		
1971		

re not available for with Marshall and ors etc. have been

able for purchase by

and Policy Division sment Management ncy 11th Avenue hewan S4P 0J8

) 924-8000 67-SAMA (7262) 924-8070

est@sama.sk.ca

www.sama.sk.ca



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment

Subject: Comparative Cost Factor

Year	Comparative Cost Factor
1972	
1973	
1974	
1975	
1976	
1977	
1978	
1979	
1980	
1981	
1982	
1983	
1984	
1985	
1986	
1987	
1988	
1989	
1990	
1991	
1992	
1993	
1994	
1995	
1996	
1997	
1998	
1999	
2000	
2001	
2002	
2003	
2004	
2005	
2006	
2007	
2008	
2009	
2010	
2011	
2012	
2013	
2014 and newer	

This table is a derivative work based on the "Marshall Valuation Service" which is copyrighted material of Marshall & Swift/Boeckh © 2014. Unauthorized reproduction is expressly prohibited.



Well Characteristics

This section describes the formulas, rules and procedures for determining the classification of resource production equipment located at an oil or gas well site. Oil and gas well resource production equipment shall be classified in accordance with the following well characteristics:

Well Area	Depth
Well Type	Rated Volume
Crude Type	Facility Type
Horizontal Completion	Days Operated

Well Area

The well areas shall be:

Well Area (Abbreviation)	Description
Weyburn (WE)	All municipalities east of the third meridian, from
weyburn (wE)	R.M. 1 to R.M. 371 inclusive, except R.M. 282.
Swift Current (SC)	All municipalities west of the third meridian, from
Switt Current (SC)	R.M. 43 to R.M. 261 inclusive.
	All municipalities west of the third meridian, from
Kindersley (KD)	R.M. 282 to R.M. 382 inclusive, including R.M.
	282 and R.M. 372.
North Pattleford South (NP S)	All municipalities from R.M. 394 to R.M. 555
Norui Battieroru - Soutii (INB-S)	inclusive.
North Pattlaford North (NP N)	All municipalities from R.M. 561 to R.M. 622
Norui Battieford - Norui (INB-IN)	inclusive and the Northern Administrative District.

Well Type

The well types shall be:

Oil	Gas Injection
Oil (New)	Continuous Steam Injection
Gas	Cyclic Steam Injection
Gas (New)	Water Source
Air Injection	Water Source (New)
Water Injection	

Oil (New) and Gas (New) wells are those wells located on a new well site that was drilled in the 12 month period ending July 1 of the year immediately preceding the year to which the assessment roll relates.



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment

Subject: Well Classification

Crude Type

The crude types shall be:

Light Medium Heavy

Horizontal Completion:

The horizontal completion types shall be: Vertical Horizontal

<u>Depth</u>

The depth of an oil or gas well shall be determined by measuring the distance from the kelly bushing to the average depth of the perforations in the well casing, or in the case of a horizontal well, the distance from the kelly bushing to the kick off depth.

Rated Volume

The volume for an oil well shall be determined based on the combined volume of oil and water produced.

The volume for a water source well shall be determined based on the volume of water produced.

The period July 1 to June 30 of the year immediately preceding the year to which the assessment roll relates, shall be used to determine the volume and days operated.

The rated volume shall be determined by application of the following formula:

 $RV = volume \div days operated$

	J 1		
where:	RV	=	rated volume
	volume	=	number of barrels of oil and/or water produced by the well
	days operated	=	number of days the well was operated

Facility Type

The facility types shall be:

Туре	Description
Tanks	Used to store oil on site until it is transferred to a battery.
Flow Lines	Used to transfer oil directly to a battery or gas directly to a gas plant, satellite or compressor station.

Days Operated

The number of days that the well was operated during the period July 1 to June 30 of the year immediately preceding the year to which the assessment roll relates.

Shut-In Well Site Reporting Period

The shut-in well site status shall be determined from the 12 month period ending September 1 of the year immediately preceding the year to which the assessment roll relates.

Pumping Units

All oil well pumping units shall be conventional or hydrabeam.



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment

Subject: Well Classification

Water Handling Equipment

Туре	Description	Rate (\$)
1	 20% of Metering Cabinet 10% - 125 - 260psi 12"x5' vertical two phase Separator 60% - 2" receiving and launching trap without bypass 70% - Test Leads 	11,600
2	 125 - 260psi 24"x10' vertical two phase separator 3" receiving and launching trap with bypass 	54,150

Metering Equipment

Туре	Description	Rate (\$)
1	 One 300psi gas, dry flow recorder chart 100" with 2 pens 50% of one 3" 300psi senior quick change 50% of one 3" 300psi simplex 	12,380

Water Handling Buildings

Туре	Description	Rate (\$)
	• 10% - 8' height, 64 sq.ft. metal shed with lining and	
1	insulation, floor and heat	
1	• 20% of 50% 40 barrel open top plastic pop tank	1,370
	• 20% of 50% 120 barrel open top plastic pop tank	
	• 8' height, 64 sq.ft. metal shed with lining and insulation,	
2	floor and heat	42,800
	• 300 barrel lap welded steel stock tank with open top	

Chemical Equipment

Туре	Description	Rate (\$)
1	• Alcohol drip (9 imp. gal. tank)	1,600



Subject: Well Classification

Substitute Well Features: Weyburn Well Area - Light Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical Wells
 - New wells ... 160 pumping unit
 - All other vertical well pumping units:

Rated Volume		Depth (ft.)			
(barrels/day)	<3000	3000-4799	4800-5700	>5700	
< 3	40	114	114	228	
3 - 9.9	57	114	114	228	
10 - 74.99	57	160	160	320	
75 - 119.99	80	160	228	320	
120 - 199.99	PC-120	228	320	456	
≥ 200	PC-120	320	456	640	
Rated volume = oil per day + (water per day \div 2)					

2. Horizontal Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 - 199.99	228	
200 - 299.99	456	
300 - 449.99	456	
450 - 599.99	640	
≥ 600 912		
Rated volume = oil per day + (water per day \div 2)		

3. Prime Mover ... electric motor.

Wellhead Assembly

Vertical ... threaded 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 2⁷/₈" tubing plain steel; ³/₄" rod Horizontal ... 2⁷/₈" tubing plain steel; ³/₄" rod Length ... depth of well for first tubing string ... depth of well minus 200 ft. for each additional tubing string

<u>Well Accessories</u> Cathodic protection rectifier.

<u>Building</u> n/a



Subject: Well Classification

Substitute Well Features: Weyburn Well Area- Medium Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical wells
 - New wells ... 160 Pumping unit
 - All other vertical well pumping units:

Rated Volume	Depth (ft.)					
(barrels/day)	< 3000	3000-4799	4800-5700	> 5700		
< 3	40	114	114	228		
3 - 9.9	57	114	114	228		
10 - 74.99	57	160	160	320		
75 - 119.99	80	160	228	320		
120 - 199.99 PC-120 228 320 456						
≥ 200	PC-120	320	456	640		
Rated volume = oil per day + (water per day \div 2)						

2. Horizontal Wells

- New wells... 640 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 - 199.99	228	
200 - 299.99	456	
300 - 449.99	456	
450 - 599.99	640	
≥ 600	912	
Rated volume = oil per day + (water per day \div 2)		

3. Prime Mover ... electric motor.

Wellhead Assembly

Vertical ... threaded 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 2⁷/₈" tubing plain steel; ³/₄" rod Horizontal ... 2⁷/₈" tubing plain steel; ³/₄" rod Length ... depth of well for first tubing string ... depth of well minus 200 ft. for each additional tubing string

<u>Well Accessories</u> Cathodic protection rectifier.

<u>Building</u> n/a



Subject: Well Classification

Substitute Well Features: Swift Current Well Area - Light Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications.

Pumping Equipment

- 1. Vertical wells
 - New wells ... 40 pumping unit
 - All other vertical well pumping units:

Rated Volume		Depth (ft.)		
(barrels/day)	< 2000	2000-4500	> 4500	
< 1.7	25	40	40	
≥ 1.7 25 40 40				
Rated volume = oil per day + (water per day \div 0.67)				

2. Horizontal Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 - 199.99	228	
200 - 299.99	456	
300 - 449.99	456	
450 - 599.99	640	
≥ 600 912		
Rated volume = oil per day + (water per day \div 2)		

3. Prime Mover... electric.

Wellhead Assembly

Vertical... threaded 2000 lbs. Horizontal... flanged 2000 lbs.

Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 2⁷/₈" tubing plain steel; ⁵/₈" rod Horizontal ... 2⁷/₈" tubing plain steel; ³/₄" rod Length ... depth of well for first tubing string ... depth of well minus 200 ft. for each additional tubing string

Building

n/a



Subject: Well Classification

Substitute Well Features: Swift Current Well Area - Medium Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical Wells
 - New wells ... 114 pumping unit
 - All other vertical well pumping units:

Rated Volume	Depth (ft.)			
(barrels/day)	< 2000	2000-4500	> 4500	
< 7	40	114	114	
7 - 190	57	114	114	
> 190 228 228 228				
Rated volume = oil per day + (water per day \div 1.5)				

2. Horizontal Wells

- New wells ... 640 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 - 199.99	228	
200 - 299.99	456	
300 - 449.99	456	
450 - 599.99	640	
≥ 600 912		
Rated volume = oil per day + (water per day \div 2)		

3. Mover ... electric motor.

Wellhead Assembly

Vertical ... threaded 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 2⁷/₈" tubing plain steel; ⁵/₈" rod Horizontal ... 2⁷/₈" tubing plain steel; ³/₄" rod Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

Building

n/a



Subject: Well Classification

Substitute Well Features: Swift Current Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

1. Vertical wells

- New wells ... 160 pumping unit
- All other vertical well pumping units ... 160 pumping unit
- Related Volume = oil per day

2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 - 499	PC-64	
> 499 PC-80		
Rated volume = oil per day + (water per day \div 7)		

3. Prime Mover ... electric motor.

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

Wellhead Assembly

Vertical ... flanged 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

Tubing and Rods

Vertical ... 3 ¹/₂" tubing plain steel; 1" rod

Horizontal ... 3¹/₂" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	7,410
Flow Line	n/a	



Subject: Well Classification

Substitute Well Features: Kindersley Well Area - Light Crude Oil

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical Wells
 - New wells ... 40 pumping unit
 - All other vertical pumping well units:

Rated Volume	Depth (ft.)		
(barrels/day)	< 2000	2000-4500	> 4500
< 1.7	25	40	40
<u>></u> 1.7	25	40	80
Rated volume = oil per day + (water per day \div 0.67)			

2. Horizontal Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 - 199.99	228	
200 - 299.99	456	
300 - 449.99	456	
450 - 599.99	640	
≥ 600	912	
Rated volume = oil per day + (water per day \div 2)		

3. Prime Mover... electric motor.

Wellhead Assembly

Vertical ... threaded 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 2³/₈" tubing plain steel; ⁵/₈" rod Horizontal ... 2⁷/₈" tubing plain steel; ³/₄" rod Length ... depth of well for first tubing string ... depth of well minus 200 ft. for each additional tubing string

Building

n/a



Subject: Well Classification

Substitute Well Features: Kindersley Well Area- Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

1. Vertical Wells

- New wells ... 160 pumping unit
- All other vertical well pumping units ... 160 pumping unit
- Rated Volume = oil per day

2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 - 499	PC-64	
>499 PC-80		
Rated volume = oil per day + (water per day \div 7)		

3. Prime Mover ... electric motor.

Facility Type	Prime Mover
Tank	Gas motor
Flow Line	Electric motor

Wellhead Assembly

Vertical ... flanged 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

Tubing and Rods

Vertical ... 2 ⁷/₈" tubing plain steel; ⁷/₈" rod

Horizontal ... 3¹/₂" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	7,410
Flow Line	n/a	



Substitute Well Features: North Battleford (South) Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical Wells
 - New wells ... PC-15 pumping unit
 - All other vertical well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 30	PC-10	
30 - 79.99	PC-15	
80 - 119.99	PC-28	
120 - 179.99	PC-54	
≥ 180 PC-64		
Rated volume = oil per day + (water per day \div 3)		

2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 - 499	PC-64	
>499 PC-80		
Rated volume = oil per day + (water per day \div 7)		

3. Prime Mover... electric motor.

Facility Type	Prime Mover
Tank	Gas motor
Flow Line	Electric motor

Wellhead Assembly

Vertical ... flanged 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

Tubing and Rods

Vertical ... 3 ¹/₂" tubing plain steel; 1" rod

Horizontal ... 3¹/₂" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	7,410
Flow Line	n/a	



Substitute Well Feature: North Battleford (North) Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical Wells
 - New wells ... PC-15 pumping unit
 - All other vertical well pumping units:

Rated Volume	Depth (ft.)		
(barrels/day)	<1000	1000-2000	>2000
< 9.0	40	80	PC-15
<u>> 9.0</u>	57	PC-15	PC-15
Rated volume = oil per day + (water per day \div 3)			

2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 - 499	PC-64	
>499 PC-80		
Rated volume = oil per day + (water per day \div 7)		

3. Prime Mover ... electric motor.

Facility Type	Prime Mover
Tank	Gas motor
Flow Line	Electric motor

Wellhead Assembly

Vertical ... flanged 2000 lbs. Horizontal ... flanged 2000 lbs. Dual wellhead for multizone completion.

Tubing and Rods

Vertical ... 3 ¹/₂" tubing plain steel; 1" rod

Horizontal ... 3¹/₂" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	7,410
Flow Line	n/a	



Substitute Well Features: Swift Current Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications	
	• 1" diameter, plastic	
Tubing	• Length: depth of well for first tubing	string, depth of
	well minus 200 ft. for each additional	tubing string
Wallboad assambly	• Threaded, 1000 pound pressure.	
wennead assembly	Dual wellhead for multi-zone completions.	
Chemical Equipment	60% of Type 1	
Water handling buildings	100% of Type 1	
Water handling equipment	100% of Type 1	
Metering equipment	10% of Type 1	
Rated Volume = gas per day	l Volume = gas per day	
Total Rate (\$)	Threaded, 1000 pound pressure 29,010	
(Except tubing and flow line)	Dual wellhead 30,800	

Substitute Well Features: Kindersley Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Description	
	• 2 ³ / ₈ " diameter, plain steel	
Tubing	• Length: depth of well for first tubing	string, depth of
	well minus 200 ft. for each additional	tubing string
Wallbaad assambly	Threaded, 2000 pound pressure	
wennead assembly	 Dual wellhead for multi-zone completions 	
Chemical equipment	None	
Water handling buildings and	65% of Turne 2	
equipment	05% of Type 2	
Metering equipment	80% of Type 1	
Rated volume = gas per day		
Total Rate (\$)	Threaded, 2000 pound pressure	92,530
(Except tubing and flow line)	Dual wellhead 94,790	



Substitute Well Features: North Battleford (South) Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications	
	 2³/₈" diameter, plain steel Length: depth of well for first tubing string, depth of 	
Tubing		
	well minus 200 ft. for each additional	tubing string
Wallbaad assambly	Threaded, 2000 pound pressureDual wellhead for multi-zone completions	
wennead assembly		
Chemical equipment	Alcohol drip	
Water handling buildings and	55% of Tupe 2	
equipment	55% of Type 2	
Metering equipment	80% of Type 1	
Rated volume = gas per day		
Total Rate (\$)	Threaded, 2000 pound pressure	84,440
(Except tubing and flow line)	Dual wellhead	86,700

Substitute Well Features: North Battleford (North) Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications	
	 2³/₈" diameter, plain steel Length: depth of well for first tubing string, depth of 	
Tubing		
	well minus 200 ft. for each addition	al tubing string
Wallbaad assembly	• Flanged, 2000 pound pressure	
wennead asseniory	• Dual wellhead for multi-zone completions	
Chemical equipment	Alcohol drip	
Water handling buildings and	48% of Type 2	
equipment	48% 01 Type 2	
Metering equipment	80% of Type 1	
Rated volume = gas per day		
Total Rate (\$)	Flanged, 2000 pound pressure	79,450
(Except tubing and flow line)	Dual wellhead	86,740





Substitute Well Features: Air, Water and Gas Injection Wells

The resource production equipment required to operate a substitute air, water or gas injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
	• 2 ⁷ / ₈ " tubing, plain steel		
Tubing	• Length: depth of well for first tubing str	ring, depth of well	
	minus 200 ft. for each additional tubing	string	
Wellhead assembly	Threaded, 2000 pound pressure		
Metering equipment	1 - 2" floco meter		
Control volvos	1 - 3" choke		
Control valves	1 - pressure control switch		
All wells east of the third meridian: Cathodic protection		odic protection	
well accessories	rectifier		
Building	20 sq.ft. fibreglass wellhead shelter		
Total Rate (\$)	All wells east of the third meridian 54,640		
(Except tubing and flow	All walls wast of the third maridian (10.960)		
line)	All wens west of the unite meridian 40,800		

Substitute Well Features: Continuous Steam Injection Wells

The resource production equipment required to operate a substitute continuous steam injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications	
	• 3 ¹ / ₂ " tubing, lined	
Tubing	• Length: depth of well for first tubing string, depth of well	
	minus 200 ft. for each additional tubing string	
Wellhead assembly	Flanged, 3000 pound pressure	
Metering equipment	1 - 3" turbine meter and totalizer	
Control valves	1 - 3" choke	
Total Rate (\$) (2 400		62 400
(Except tubing)	Except tubing) 03,400	



Substitute Well Features: Cyclic Steam Injection Wells

The resource production equipment required to operate a substitute cyclic steam injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications	
	• 3 ¹ / ₂ " tubing, lined; 1" rods	
Tubing and rods	• Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string	
Dumping aquinment	67% of a conventional 160 pumping unit with electric	
Fumping equipment	motor	
Wellhead assembly	Flanged, 3000 pound pressure	
Metering equipment	3 - 3" turbine meters and totalizers	
Control valves	1 - 3" choke	
Total Rate (\$)		160 200
(Except tubing and rods and flow line)		109,200



Section: **Resource Production Equipment**

Well Classification Subject:

Substitute Well Features: Water Source Wells

The resource production equipment required to operate a substitute water source well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Tubing and Rods

- 1. New Wells
 - 2⁷/₈" tubing, plain steel; ⁷/₈" rod
 - Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string
- 2. Rated volume <150,000 imp. gal./day
 - $2\frac{7}{8}$ " tubing, plain steel; $\frac{7}{8}$ " rod
 - Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string
- 3. Rated volume >150,000 imp. gal./day
 - 2⁷/₈" tubing plain steel
 - Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string for ٠ depth of well

		Specifications	
	Description	New Wells and Wells Rated Volume <150,000 imp. gal./day	Rated Volume ≥150,000 imp. gal./day
	Pumping equipment	 PC-15 pumping unit 50% of 1 - variable frequency drive 	 Submersible pumping unit 400 series 100 stage Submersible pump motor 456 series 80 hp Switchboard 100 hp Transformer 75 kva Size 4 submersible pump cable x well depth x 1.05 50% of 1 - variable frequency drive
	Wellhead assembly	Threaded, 2000 pound pressure	Threaded, 2000 pound pressure
	Metering equipment	None	None
	None	 1 - 3" choke 1 - pressure control switch 	 1 - 3" choke 1 - pressure control switch
	Manifold	None	None
	Well Accessories: Cathodic Protection	All wells east of the third meridian	All wells east of the third meridian
	Building	None	20 sq.ft. fibreglass wellhead shelter with heat
Total Rate (\$)	All wells east of the third meridian	138,620	212,730
(Except tubing, rod and cable and flow line)	All wells west of the third meridian	124,840	198,950



Substitute Well Features: Heavy Crude Steam Assisted Gravity Drainage (SAGD) Oil Wells (entire Province)

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

Pumping Equipment

- 1. Vertical SAGD Wells
 - New wells ... PC-15 pumping unit
 - All other vertical well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 30	PC-10	
30 - 79.99	PC-15	
80 - 119.99	PC-28	
120 - 179.99	PC-54	
≥ 180	PC-64	
Rated volume = oil per day + (water per day \div 3)		

2. Horizontal SAGD Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 - 499	PC-64	
500 - 599	320	
600 - 799	456	
> 800	640	
Rated volume = oil per day + (water per day \div 7)		

3. Prime Mover... electric motor.

Facility Type	Prime Mover
Tank	Gas motor
Flow Line	Electric motor

Wellhead Assembly Vertical ... flanged 3000 lbs. Horizontal ... flanged 3000 lbs. Dual wellhead for multizone completion.

<u>Tubing and Rods</u> Vertical ... 3 ¹/₂" tubing plain steel; 1" rod Horizontal ... 4¹/₂" tubing plain steel; 1" rod Length ... depth of well for first tubing string ... depth of well minus 200 ft. for each additional tubing string

Facility Type	Building	Rate (\$)
Tank	64 sq.ft. pump shack	7,410
Flow Line	n/a	



Subject. Wen Head Assembly

Description

A typical well head assembly is made up of a casing head, tubing head and Christmas tree. The well head may be screwed onto the casing or it may be an assembly that is bolted together. These are called the threaded or flanged well heads respectively.

Rates

The rates for well head assembly are dollars per unit.

	Size				
Туре	Series 400 W.P. ≤ 1000 psi	Series 600 W.P. 2000 psi	Series 900 W.P. 3000 psi	Series 1500 W.P. 5000 psi	
Pumping Oil					
Single Flanged	14,780	17,120	17,810	29,070	
Single Threaded	13,010	14,870	15,440	24,780	
Dual Flanged	26,030	30,190	31,970	32,340	
Dual Threaded	14,720	23,240	27,710	27,570	
Flowing Oil & Gas					
Single Flanged	17,050	21,410	27,890	27,930	
Single Threaded	13,640	19,600	25,240	25,470	
Dual Flanged	23,660	28,700	33,820	33,840	
Dual Threaded	15,430	21,870	24,560	24,620	
Injection - Air, Gas of	r Water				
Flanged	17,120	21,410	28,390	28,400	
Threaded	13,530	19,600	25,620	25,470	
Dual Threaded	15,430	21,870	24,560	24,620	
Injection - Steam					
Flanged	37,360	37,370	37,370	37,370	
Steam Injection & Pumping					
Flanged	53,380	53,460	53,410	53,300	
Tubingless (Casing H	ead)				
Flanged	13,520	14,920	14,780	15,060	
Threaded	9,010	9,580	9,960	10,200	





Subject: Pumping Units

Conventional and Hydrabeam

This is the typical horsehead or grasshopper counterbalance unit. The rods are raised by carrier bar at the horsehead end of the waling beam. On the downstroke, the weight of the rod assembly is counterbalanced by large weights. The picot point of the assembly is in the middle of the walking beam.

<u>Rates</u>

The rates for conventional and hydrabeam pumping units are in dollars per unit.

Gear Box Torque	Without Prime	El	ectric	G	as
Rating (x 1000) (lb.)	Mover (2)	Prime	Prime Mover (1)		lover (1)
		Rate	Range (hp)	Rate	Range (hp)
25	35,750	52,230	5	85,990	9 - 12
40	39,660	55,460	6	88,620	9 - 12
57	47,910	65,630	5 - 10	101,750	9 - 12
80	51,230	70,100	5 - 10	112,130	9 - 19
114	85,930	106,230	7.5 - 15	152,510	13 - 19
160	93,250	116,390	15 - 25	167,840	20 - 29
228	110,480	136,450	20 - 40	200,900	20 - 39
320	130,310	162,890	30 - 60	244,810	30 - 59
456	164,540	200,180	40 - 75	295,100	40 - 99
640	192,170	228,990	50 - 75	357,420	60 - 99
912	224,030	264,640	60 - 100	423,760	60 - 149
1280	366,150	407,710	70 - 125	568,950	100 - 199
Rates include:					
- prime mov	ver where noted		- polish rod		
- belt			- beam chemica	l injector at 50%	
- rod rotator	•		- counter weight	ts	
- concrete b	ase		- pressure switch	h	
- bottom ho	le pump		 stuffing box 		
- frame exte	ension and side rails		- installation		
NOTE: 1) Costs includ	e:				
- per	electrified site - \$9,6	00			
- per gas operated site - propane vessel and/or scrubber with self-feed gas at \$11.760					
2) Cost withou	2) Cost without Prime Mover:				
- ele	ctrical and propane ve	essel costs are not i	ncluded and must be	added if these ra	tes are used.
- app	bly these rates to non-	typical installation	S		
Strap jacks a	3) Strap jacks and slant jacks:				
- inc	rease conventional pu	mping unit cost by	/ 20%		



Subject: Pumping Units

Unitorque and Air- Balanced Beam

The entire walking beam for unitorque and air-balanced beam pumping units moves up and down with the pivot point at the end of the beam. Unitorque pumping units have a counterweight system similar to conventional pumping units. The air-balanced beam pumping units have no counterweights. The downstroke is cushioned by a very large air-supplied "shock absorber". There will be a small compressor mounted on the pumping unit to feed the unit.

Rates

The rates for unitorque and air-balanced beam pumping units are dollars per unit.

Coor Dor		Elec	tric	G	as
Gear Box		Prime M	over (1)	Prime M	lover (1)
(v 1000) (lb.)	Mover (2)	Pate	Range	Rate	Range
(X 1000) (ID.)	WIOVEI (2)	Kate	(hp)	Kate	(hp)
114	93,700	115,100	7.5 - 15	154,400	13 - 19
160	114,420	138,450	15 - 25	190,730	20 - 29
228	131,550	160,640	20 - 40	223,690	20 - 39
320	158,080	191,690	30 - 60	274,870	30 - 59
456	185,750	222,510	40 - 75	318,870	40 - 99
640	206,600	244,460	50 - 75	374,640	60 - 99
912	253,810	296,300	60 - 100	457,480	60 - 149
Rates include:					
- prime mover	where noted		- polish r	od	
- belt			- beam cl	hemical inject	tor at 50%
- rod rotator			- counter	weights	
- concrete bas	e		- pressure	e switch	
- bottom hole	pump		- stuffing	box	
 frame extens 	ion and side ra	ils	- installa	tion	
NOTE: 1) Costs	include:				
- per	electrified site	- \$9,570			
- per	gas operated si	ite - propane vo	essel and/or so	crubber with s	self-feed gas
at \$11,720					
2) Cost without Prime Mover:					
- electrical and propane vessel costs are not included and must be added					
if these rates are used					
- apply these rates to non-typical installations					



Subject: Pumping Units

Submersible Pumping Equipment

Submersible pumps have the major working system suspended at the bottom of the well bore inside the tubing. This system is identified on the surface by heavy electric cable emerging from the top of the wellhead.

Motor Rates

The motor rates for submersible pumping equipment are in dollars per unit.

Rating (hp)	Rate			
Series	375	456	540	
Minimum Casing	41/2"	5½"	6 ⁵ /8"	
7.5	37,910	34,810		
10	44,630	37,270		
15	50,200	41,580		
19.5	53,850	45,850		
22.5	56,910	48,920		
25	64,210	50,790		
30		55,030	43,500	
40		63,500	47,030	
50		72,190	53,150	
60		75,720	60,430	
70		83,700	65,370	
80		91,710	70,900	
90		99,700	75,840	
100		107,710	80,070	
110		116,170	85,600	
120		124,160	91,010	
130			96,530	
150			106,400	
160			111,940	
180			122,280	
200			133,220	
225			144,860	
 NOTE: 1) Series number refers to outside diameter size of motor or pump, eg. series 456 is 4.56 inches O.D. 2) Motors and pumps can be stacked, eg. in 4¹/₂" casing, to achieve 100 hn 4 - 25 hn motors are stacked. 			tor or pump, eg. g, to achieve 100	
3) Generally, the	pump is the value	of the motor. This	s can be used as a	
guide if proper size information is not available.				



Subject: Pumping Units

Pump Rates

The pump rates for submersible pumping equipment are in dollars per unit.

Stages	Length (ft.)	Rate			
S	eries	338	400	540	540
Barr	els/Day	400-1500	280-4000	2000-7000	10000
Minim	um Casing	41/2"	51/2"	65/8"	65/8"
<u><</u> 20	2.1	12,730	12,600	12,520	12,470
21 - 40	3.5	15,890	12,830	16,330	22,700
41 - 60	4.9	19,150	15,070	19,000	26,570
61 - 80	6.3	22,360	17,640	21,540	30,460
81 - 100	7.8	25,570	20,040	24,220	34,230
101 - 120	9.1	28,660	22,420	26,790	39,570
121 - 140	10.5	31,870	24,870	29,410	41,990
141 - 160	11.9	35,090	27,180	31,960	45,730
161 - 180	13.3	38,300	29,600	34,630	49,520
181 - 200	14.7	41,520	32,080	37,180	53,380
201 - 220	16.1		34,450	39,820	57,330
221 - 240	17.5		36,900	42,470	61,170
241 - 260	18.9			47,590	65,030
261 - 280	20.4			50,350	68,940
> 280	21.8			53,230	72,830

Switchboards

The switchboard rates for submersible pumping equipment are in dollars per unit.

Rating (hp)	Rate
25	13,600
50	15,280
100	17,650
200	26,860
1000	44,650
1500	45,860
2000	47,090



Subject: Pumping Units

Transformers

The transformer rates for submersible pumping equipment are in dollars per unit.

Size (kVA)	Rate
50	11,120
75	11,730
100	15,430
125	16,670
150	20,380
200	29,020
250	31,490

Cable

The cable rates for submersible pumping equipment are in dollars per linear foot.

Size	Power (hp)	Rate
1	> 200	30.33
2	150 - 200	26.51
4	< 150	19.82

Progressive Cavity (PC)

Pump Rates

The pump rates for progressive cavity pumping equipment are in dollars per unit.

Size M ³ /100 rpm	Rate		
10	67,740		
12	69,390		
15	71,600		
28	75,160		
54	81,150		
64	88,080		
80	91,010		
95 92,900			
120 110,440			
Rates Include:			
- drive system (gas or	electric prime mover,		
hydraulic or electric skid)			
- bottom hole pump (r	- bottom hole pump (rotor, stator)		
- installation			

Variable Frequency Drive

The rate for a variable frequency drive shall be \$50,020 per unit.





Subject: Prime Movers

Description

Prime movers include electric and gas motors used to provide power to pumping units.

Triple-Rated Motors

The triple-rated motor prime mover rates are in dollars per unit.

	Size	Controller	Dete
(hp)	(k w)	Size	Kate
10 / 7.5 / 5	7.5 / 5.6 / 3.7	1	7,840
15 / 10 / 7.5	11.2 / 7.5 / 5.6	2	10,380
20 / 15 / 10	14.9 / 11.2 / 7.5	2	11,630
25 / 20 / 15	18.6 / 14.9 / 11.2	2	13,390
30 / 22 / 15	22.4 / 18.6 / 11.2	3	14,920
40 / 30 / 20	29.8 / 22.4 / 14.9	3	18,460
50 / 40 / 30	37.3 / 29.8 / 22.4	3	21,160
60 / 50 / 40	44.8 / 37.3 / 29.8	4	24,600
75 / 60 / 50	56 / 44.8 / 37.3	4	26,840
100 / 75 / 60	74.6 / 56 / 44.8	4	30,680
125 / 100 / 75	93.3 / 74.6 / 56	4	32,400
Rates include:			
- 3 phase		- controller	
- 1200 RPM		- 460 volt	
- fan-cooled motor		- totally encl	losed
- 60 Hz		- installation	l
- class F	insulation		



Subject: Prime Movers

Single-Rated Motors

The single-rated motor prime mover rates are in dollars per unit.

Size (hp)	Rate		
1 - 2	5,780		
3 - 5	6,010		
7.5 - 10	6,760		
15 - 20	9,040		
25 - 30	11,800		
40	14,030		
50	14,880		
60	17,780		
75	19,820		
100	27,020		
125	30,950		
150	34,850		
200	47,290		
250	56,590		
Rates include:			
- 3 phase	- controller		
- 1200 RPM	- 460 volt		
- fan-cooled motor	 totally enclosed 		
- 60 Hz	- installation		
- class F insulation			

Gas Engines

The gas engine prime mover rates are in dollars per unit.

Group #	Size (hp)	Rate		
1	9 - 12	36,340		
2	13 - 19	45,560		
3	20 - 29	61,240		
4	30 - 39	76,710		
5	40 - 59	100,160		
6	60 - 99	115,480		
7	100 - 149	183,280		
8	150 - 199	188,410		
NOTE: Deduct \$3,460 if no electric start in groups #1 to #4.				
Rates include:				
- twin-disk cl	utch	-	power take off	
- condensing radiator with fan		-	heavy flywheel	
- pressure lubrication		-	regulator	
- combination gas-gasoline carburetor		-	air cleaner	
 adjustable sub-base 		-	engine starter	
 miscellaneous pipe fittings 		-	installation	


Subject: Tubing and Kods

Description

The bottom hole pump is suspended from the surface by a series of 20 foot steel or fibreglass rods that are threaded together. The most common size for the tubing is $2\frac{7}{8}$ inches (plain) in diameter and for the rod it is $\frac{7}{8}$ inches in diameter.

Rates

The rates for tubing and rods are dollars per lineal foot.

Tubing

Size (in)	St		
Size (III.)	Plain	Lined	Plastic
$\leq 1^{1/2}$	5.54		1.96
2	6.16		
23/8	6.68	7.45	
27/8	7.62	13.49	
31/2	10.63	14.64	
4	14.25	18.32	
41/2	19.19	23.53	

Rods

Size (in.)	Rate
5/8	2.66
3⁄4	3.32
7⁄8	4.18
1	5.03





Subject. Separators and freater

Description

A separator is a vertical, spherical or horizontal vessel through which the emulsion is passed to split liquids and gases. Centrifugal action created by baffles inside the unit causes the split to occur.

Vertical Two-Phase Separators

A treater is a vessel that heats the emulsion to finalize the field separation cycle.

The rates for separators are in dollars per unit.

	Height (ft.)			
Diameter (In.)	5	7.5	10	15
125-260 psi Working Pressure				
≤ 16	21,670	22,820	23,940	26,070
24	37,020	38,880	40,990	44,400
30	49,900	50,870	53,410	58,250
36	52,340	62,920	66,050	71,930
42	71,230	74,860	78,660	85,740
48	82,660	86,930	91,280	99,500
54	94,100	98,900	103,890	113,340
60	105,620	110,960	116,560	127,080
500-1000 psi Working Pressure				
≤ 16	25,500	26,840	28,160	30,770
24	42,510	46,200	48,480	52,850
30	59,700	60,810	63,950	69,530
36	71,770	75,330	79,080	86,210
42	85,660	89,920	94,330	102,880
48	111,150	104,430	109,670	119,560
54	113,410	119,020	140,170	136,220
60	127,000	133,480	145,660	152,920
1200-1440 psi Working Pressure				
<i>≤</i> 16	27,500	28,940	30,400	33,120
24	23,210	50,470	53,060	57,900
30	63,440	66,110	70,040	76,460
36	77,010	80,940	85,030	94,900
42	94,250	99,060	104,000	113,460
48	109,690	115,240	121,010	131,960
54	125,050	131,430	137,970	150,570
60	140,440	147,630	155,070	169,090
Rates include:				
- 1 oil dump valve		- 1gauge glass assembly		
- 1 liquid level controller		- 1 safety relief valve		
- 1 pilot gas supply regulator	- 1 pressure guage			



Resource Production Equipment

Subject: Separators and Treaters

Vertical Three-Phase Separators

The rates for vertical three-phase separators are in dollars per unit.

	Height (ft.)			
Diameter (in.)	5	7.5	10	15
125-260 psi Working Pressure				
≤ 16	36,460	41,290	46,090	55,540
20	40,100	46,510	52,760	65,330
24	50,030	52,920	54,080	63,300
30	52,170	60,280	61,810	64,610
36	53,250	61,940	63,120	65,330
42	75,120	82,820	84,560	87,310
500-1000 psi Working Pressure				
≤ 16	44,190	45,320	46,690	48,970
20	50,150	51,490	53,000	55,660
24	51,690	55,300	60,740	70,820
30	58,790	60,750	76,340	105,700
36	60,800	70,360	87,650	122,180
42	81,260	99,190	123,630	172,220
1200-1440 psi Working Pressure				
≤ 16	45,180	47,120	49,190	53,150
20	56,420	59,680	63,090	69,630
24	60,210	62,170	64,350	78,580
30	63,990	67,280	81,350	109,400
36	75,230	84,240	93,380	111,320
42	103,620	116,050	128,750	153,480
Rates include:	, , , , , , , , , , , , , , , , , , , ,			
- 2 oil and water dump valves	- 1 safety relief valve			
- 1 oil level controller	- 1 pressure gauge			
- 1 pilot gas supply regulator	- 1 water level controller		troller	
- 1 gauge glass assembly				



Resource Production Equipment

Subject: Separators and Treaters

Horizontal Two-Phase Separators

The rates for horizontal two-phase separators are in dollars per unit.

Diamatan (in)	Length (ft.)			
Diameter (In.)	8	10	15	
125-260 lb. Working Pressure				
≤ 16	34,670	35,530	37,280	
20	37,450	38,350	40,320	
24	42,660	43,640	46,010	
30	42,780	46,350	48,840	
36	51,800	53,060	55,870	
42	56,490	57,830	60,990	
48	61,530	62,990	66,300	
54	66,450	68,130	71,960	
60	71,490	73,290	77,380	
500-1000 lb. Working Pressure				
< 16	35,750	36,700	38,840	
20	37,730	40,700	42,870	
24	45,240	46,350	48,840	
30	48,520	49,760	52,380	
36	57,430	58,700	61,860	
42	62,820	64,230	67,720	
48	68,910	70,590	74,440	
54	75,120	76,930	81,140	
60	81,330	83,290	87,770	
1200-1440 lb. Working Pressure				
≤ 16	42,940	43,880	45,680	
20	53,680	54,730	56,910	
24	54,270	55,360	57,800	
30	63,180	64,420	67,120	
36	81,460	83,080	86,590	
42	88,510	90,300	94,130	
48	99,040	101,050	105,390	
54	109,580	111,810	116,480	
60	120,130	122,580	127,760	
Rates include:				
- 1 oil dump valve	- 1 gauge glass assembly			
- 1 liquid level controller	- 1 safety relief valve			
- 1 pilot gas supply regulator	- 1 pressure gauge			



Section:

Resource Production Equipment

Subject: Separators and Treaters

Horizontal Three-Phase Separators

The rates for horizontal three-phase separators are in dollars per unit.

	Length (ft.)			
Diameter (in.)	8	10	15	
125-260 lb. Working Pressure				
≤ 16	37,600	41,510	50,600	
20	42,800	47,080	57,550	
24	50,130	55,180	67,400	
30	30,280	58,850	71,930	
36	60,530	66,600	81,400	
42	73,230	80,740	98,770	
48	78,550	86,510	105,790	
54	86,270	94,860	116,020	
60	93,910	103,330	126,370	
500-1000 lb. Working Pressure				
≤ 16	37,000	40,730	49,740	
20	47,170	51,840	63,430	
24	52,020	57,190	69,970	
30	57,580	63,250	77,350	
36	66,660	73,290	89,670	
42	85,690	97,600	119,280	
48	93,510	102,760	125,900	
54	104,270 114,390		139,940	
60	114,580 126,070 15		154,100	
1200-1440 lb. Working Pressure				
≤ 16	48,000	43,810	52,720	
20	60,940	66,980	81,870	
24	61,120	67,290	82,350	
30	71,290	78,430	95,790	
36	90,490	99,560	116,980	
42	102,740	113,090	143,630	
48	113,380	124,730	152,560	
54	125,690	138,240	169,100	
60	137,990 151,860 185,590		185,590	
Rates include:				
- 2 oil and water dump valves	- 1 gauge glass assembly			
- 1 oil level controller	- 1 safety relief valve			
- I pilot gas supply regulator	tor - 1 pressure gauge			
- I water level controller				



Subject: Separators and Treaters

Spherical Separators

The rates for spherical separators are in dollars per unit.

Working Pressure (lb.)	Diameter (in.)	Rate
125	36	30,780
125	42	34,370
260	36	34,540
	42	38,490
	48	45,600

Rollo Metering Separators

The rates for rollo metering separators are in dollars per unit.

Rollo Metering - Vertical: 125 lb. working pressure				
Size (in. x ft.)	Rate Without	Rate With		
	Automatic Sampler	Automatic Sampler		
24 x 6	24,300	26,390		
30 x 6	28,280	30,800		
36 x 6	32,410	35,370		
48 x 6	37,740	41,450		
Rates include:				
- separator	- recorder			
- meter	- installation			
Pounds (force) per sq.in. x 6.894757 = kpa rating				

Treater Accessories

The rates for treater accessories are in dollars per unit.

Ignition System

Туре	Rate		
Automatic	19,140		
Manual	3,200		

Desand System

Longth (ft)	Rate			
Length (It.)	Automatic	Manual		
<u><</u> 25	83,950	12,000		
23 - 35	108,930	39,610		
36 - 45	133,930	66,730		
<u>></u> 46	158,960			

Burner

The rate for a burner shall be \$58,490 per unit.



Subject: **Separators and Treaters**

Atmospheric Treater - Coalescer Wash Tank

The rates for atmospheric treaters – coalescer wash tanks are in dollars per unit.

Size (barrels)	Rate		
<u>≤</u> 400	112,470		
750	149,940		
900	162,450		
1,000	168,710		
1,500	218,650		
2,000	231,170		
2,500	268,710		
3,000	293,740		
3,500	312,400		
4,000	324,910		
≥ 5,000 343,800			
Rates include:			
- burn and heating equipme	nt including 2 firetubes		
- lining			
 gas regulators and scrubbe 	ers		
- fittings			
- cone bottoms			
- stacks			
- flame arrestors			
- all piping			
- valves and meters			
- baffles and all necessary materials			
installation			

- installation



Subject: Separators and Treaters

Horizontal Mechanical Coalescer Treater

The rates for horizontal mechanical coalescer treaters are in dollars per unit.

Section:

Diamatan (in)	Length (ft.)			
Diameter (In.)	4	6	8	10
15-50 lb. Working Pressure				
15.5	205,170	226,240	283,930	283,930
20	243,710	243,710	322,960	323,080
22	251,140	313,410	331,100	350,730
25	262,860	262,860	340,670	418,960
30	281,780	281,780	381,130	500,720
75 lb. Working Pressure				
20		250,060	330,860	474,370
22	339,480 339,4		339,480	482,760
25		349,540	349,540	495,450
30		392,380	392,140	513,960
44		448,890	448,890	565,240
45		479,530	479,530	581,520
50		509,690	508,650	598,990
Rates include:				
- single firetube		- insulation		
- fuel gas system c/w burning equipment		- water siphon		
- ladder and crowsnest		- pressure gauge and gauge glass		
- thermometer		- gas back pressure valve		
- water and oil outlet valve		- water meter		
- relief valve		- installation		
- flame arrestor and stack anodes		- scrubber		



Resource Production Equipment

Subject: Separators and Treaters

Vertical Treater

The rates for vertical treaters are in dollars per unit.

Diamatan (in)	Length (ft.)				
Diameter (In.)	3	4	6	8	10
50 lb. Working Pressure					
20	119,380	139,480	149,530	187,570	218,190
24	121,010	142,660	154,790	197,610	230,390
28	122,130	145,940	160,050	206,230	240,920
30	123,120	148,090	162,200	210,820	247,370
75 lb. Working Pressure					
20	118,830	142,110	158,020	203,950	238,770
24	139,480	148,570	166,510	215,550	252,640
28	154,310	154,310	172,740	225,490	264,710
30	157,420	157,420	176,560	230,870	271,070
Rates include:					
- single firetube		-	insulation		
- fuel gas system c/w burr	ourning equipment -		water siph	non	
- ladder and crowsnest		pressure g	gauge and g	auge glass	
- thermometer		-	gas back j	pressure val	ve
- water and oil outlet valve		-	water met	er	
- relief valve		-	installatio	n	
- flame arrestor and stack anodes		-	scrubber		



Resource Production Equipment Subject: S

Section:

bject: Separators and Treaters

Horizontal Electrostatic Coalescer Treater

The rates for horizontal electrostatic coalescer treaters are in dollars per unit.

Diamatan (in)	Length (ft.)		
Diameter (III.)	6	8	10
50 lb. Working Pressure			
20	328,910	424,520	520,610
25	376,590	493,610	576,070
30	424,520	528,160	631,810
40	520,610	637,140	742,830
50	616,710	740,780	853,180
75 lb. Working Pressure			
20	336,940	435,230	600,170
25	386,810	507,230	625,950
30	435,230	542,030	648,580
40	534,590	622,720	710,850
50	633,000	692,610	752,210
Rates include:			
- single firetube, flame arrestor & stack		- low level	shutdown
- gas out scrubber dome		- oil and wa	ater level
- high temperature shutdown		controller	
- 1 oil and 1 gas outlet v	valve	- 2 water ou	utlet valves
- instrument air manifold c/w regulators		 relief valv 	ve
- water meter		- scrubber	
- pressure gauge and thermometer		- transform	er circuit breaker
- gauge glasses		- skid	
 pre-piping to skid edge c/w valves 		- anodes	
- ladder and transformer platformer		- insulation	
- fuel gas manifold c/w burning equipment		- installatio	n





Description

Dehydrators remove liquid from the gas to prevent corrosion or plugging of the flow.

Section:

Glycol Absorber Tower (600# ANSI Rating)

The rates for glycol absorber towers are in dollars per unit.

	Rate		
Size		Including	Including
Diameter (in.) x Length (ft.)	Standard Unit	2-Phase Inlet	3-Phase Inlet
		Scrubber	Scrubber
1400 #DWP			
12 x 12	26,950	40,480	47,650
12 x 14	28,010	41,140	48,630
12 x 16	29,050	42,720	50,000
12 x 18	29,980	43,730	50,950
12 x 20	31,030	44,740	51,910
12 x 30	35,640	48,930	57,500
1420 #DWP			•
16 x 12	32,660	48,000	57,470
16 x 14	34,280	49,340	58,790
16 x 16	35,620	50,600	60,430
16 x 18	37,230	51,910	61,690
16 x 20	38,490	53,490	63,370
16 x 30	44,610	61,090	71,160
1400 #DWP			
20 x 12	41,810	59,750	69,870
20 x 14	43,730	61,690	71,810
20 x 16	45,720	63,670	73,790
20 x 18	47,650	65,580	76,080
20 x 20	50,000	67,640	78,050
20 x 30	59,450	76,940	87,880
1380 #DWP			
24 x 12	51,910	78,050	90,240
24 x 14	56,470	82,270	94,330
24 x 16	60,720	86,570	98,920
24 x 18	64,990	90,740	102,840
24 x 20	69,200	95,290	107,430
24 x 30	89,720	115,630	127,800



Document Number 4.1.9

Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment

Subject: Dehydrators

	Rate		
Size		Including	Including
Diameter (in.) x Length (ft.)	Standard Unit	2-Phase Inlet	3-Phase Inlet
		Scrubber	Scrubber
1400 #DWP		r	ſ
30 x 12	87,360	129,180	144,800
30 x 14	93,460	135,250	150,870
30 x 16	99,640	141,400	157,340
30 x 18	106,050	147,820	163,470
30 x 20	111,490	154,060	169,260
30 x 30	140,680	183,580	198,630
36 x 12	113,510	164,510	181,160
36 x 14	121,030	172,370	188,960
36 x 16	128,430	179,790	196,420
36 x 18	130,980	187,620	203,930
36 x 20	144,110	195,100	211,540
36 x 30	180,230	231,510	247,770
42 x 20	176,680	228,880	244,300
42 x 30	212,830	264,070	280,390
Rates include: - knitted 304 stainless wire mesh mist extractor - glycol gas heat exchanger in upper section - liquid level controller with supply gas regulator - diaphragm operated liquid discharge valve with shut-off ball valve - fuel gas shut-off valve - reflex gauge column assembly with safety cocks - thermometer with thermowell - pressure gauge with isolating valve - ASME safety relief valve 1" threaded - skid and building - gas outlet line to skid edge Integral scrubber includes: - liquid level controller with supply gas regulator (2 or 3 phase) - diaphragm operated liquid discharge valve with shut-off ball valve (2 or 3			
 phase) gauge column assembly with safety cocks (reflex) cold weather coil phase drain valve (Apollo) NOTE: DWP refers to design working pressure 			



Resource Production Equipment

Subject: Dehydrators

Standard Glycol Reconcentrator Units

The rates for standard glycol reconcentrator units are in dollars per unit.

Heat Output (BTU/hr.)	Reboiler Size Diameter(in.) x Length (ft.)	Surge Tank Size Diameter(in.) x Length (ft.)	Rate
100,000	18 x 3.5	18 x 3	65,980
155,000	18 x 5.5	18 x 3.5	73,600
235,000	18 x 5.5	18 x 3.5	86,370
375,000	24 x 6.5	24 x 6	122,690
545,000	30 x 6.5	30 x 6	155,810
750,000	30 x 15	30 x 12.5	177,210
1,000,000	50 x 15	30 x 15	211,570
1,250,000	50 x 17.5	30 x 15	260,960
Rates include:			
 glycol pum 	р -	thermostats	
- flame arrest	tor -	still column	
 glycol filter 	-	equipment mounted on st	ructural steel skid
- gas firing a	ccessories -	installation	
Rates do not includ	le:		

- ladders

- gas or electric pumps
- stand-by pumps
- gas sparging or stripping accessories for high concentration glycol

Accessories (Lump Sum)

Description	Rate
Skid	
8' x 16'	9,000
9' x 22'	13,760
Ladder	5,790
Gas sparging or stripping accessories	5,970

CaCI Rollo Units

Tower Size Diameter (in.) x Length (ft.)	Rate		
22 x 15	65,100		
24 x 15	71,230		
26 x 15	73,580		
22 x 17	70,400		
24 x 17	74,470		
26 x 17	78,550		
24 x 24	82,920		
30 x 24	98,340		
Rates include:			
- pipes - fit	tings		
- valves - ins	stallation		
Rates do not include meters and chemical injectors			



nt Subject: Dehydrators



Subject: Gas Boots

Description

A gas boot is a vapour recovery system that draws gases that are being released in storage tanks.

Rates

The rates for gas boots are in dollars per unit.

Size	Dete
Diameter (in.) x Length (ft.)	Kate
16 x 5	8,030
16 x 10	11,270
16 x 20	17,660
16 x 40	33,150
16 x 50	34,840
24 x 10	25,370
24 x 20	27,780
24 x 40	33,100
24 x 50	36,420
30 x 20	49,510
30 x 40	67,490
30 x 50	76,460
36 x 35	67,160
36 x 50	84,780
NOTE: For 30 in. or 36 in. di	ameter no ladder or platform
included with rates -	add \$12,110 if present
Rates include:	
 miscellaneous pipe 	
- valves	
- fittings	
- installation	



ent Subject: Gas Boots



Subject: Flare Stacks

Description

A flare stack is used to burn off excess gas.

Rates

The rates for flare stacks are in dollars per stack.

Hoight (ft)	Rate (Diameter) (in.)		
neight (it.)	4	6	8
30 - 60	18,520	22,600	28,340
70 - 100	20,010	24,540	31,110



nt Subject: Flare Stacks



Description

These are lines of pipe used to flare gas, or transport oil and gas products from a well site to a battery or gas handling site or from a battery or gas handling site to a pipeline or truck depot.

Rates

Flare, drain and market lines are valued at \$6,310 per line.





Subject: Gas Scrubbers

Description

The gas passes through this vessel to remove liquids. It functions as a small scale separator.

Fuel Gas Scrubber

The rate for fuel gas scrubbers is in dollars per unit.

	Rate
All sizes	4,800
Rates include:	
- shut-off valve	
- pressure gauge	
- relief valve	
- installation	





Subject: Heater and Heat Exchanger

Description

Heaters and heat exchangers are used to prevent line and equipment from freezing.

Heaters

The rates for direct and indirect heaters are in dollars per unit.

Outrust Damas (DTU)	Rate		
Output Kange (BIU)	Indirect	Direct	
50,000 - 170,000	43,800	38,230	
171,000 - 375,000	44,740	39,530	
376,000 - 625,000	48,020	41,510	
626,000 - 875,000	54,460	44,740	
876,000 - 1,250,000	64,180	54,480	
1,251,000 - 1,750,000	76,080	66,360	
1,751,000 - 2,500,000	89,050	69,610	
2,501,000 - 3,500,000	108,460	102,000	
3,501,000 - 4,500,000	134,360	105,620	
Rates include:			
- fire tube			
- thief hatch			
- skid			
- temperature control and high temperature shut down			
- flame arrestor and stack			
- expansion pot c/w instruments			
- soil (not included with direct)			
- fuel gas manifold c/w burning			
- installation			



Subject: Heater and Heat Exchanger

Tubular and Rectangular Plate Heat Exchangers

The rates for tubular and rectangular plate heat exchangers are in dollars per cubic foot.

Face Area (sq.ft.)	Rate (\$/cu.ft.)
<u><</u> 2	2,275
3	2,184
4	2,122
6	1,964
8	1,806
10	1,659
12	1,552
14	1,349
Rates include:	
- standard unit s - installation	stainless steel plates
Sample Calculation:	
Face Area =	3 ft. x 4 ft.
Length =	8 ft.
Area =	3 ft. x 4 ft. x 8 ft.
=	96 cu.ft.
Rate =	\$1,552 /cu.ft.
Value =	Area x Rate
=	96 cu.ft. x \$1,552/cu.ft.
=	\$148,992



Resource Production Equipment Subject:

Description

Meters are used to calibrate the pressure and volume of gas flowing through a flow line or at a gas well.

Dry Flow Meters

The rates for dry flow meters are in dollars per unit.

Туре	Rate
Gas, Dry Flow Recorder Chart 100" (\leq 1000 psi)	
1 or 2 pen	6,060
3 pen	7,670

Meters

Orifice Fittings and Meter Runs

The rates for orifice fittings and meter runs are in dollars per unit.

Size (in.)	Rate
Senior Quick Change (100 - 600 psi)	
2	8,210
3	9,570
4	11,430
6	14,490
8	17,580
10	20,670
Simplex (150 - 600 psi)	
2	2,420
3	3,050
4	3,650
6	5,600
8	7,040
10	8,630
Rates include:	
- orifice fittings	
- regulator	
- pipes	
 valves and fitting for meter run 	
- installation	



Resource Production Equipment

Subject: Meters

Net Oil Computer and Micro Motion Meter

Inlet Size (in.)	Rate
2	42,460
3	45,640
4	49,060
Rates include:	
- capacitance probe	
- indicator	
- installation	

Positive Displacement Meter

The rates for positive displacement meters are in dollars per unit.

Line Size (in.)	Rate
Floco Meter	
≤2	5,690
3 to 4	8,390
Sampler	3,210
Sales Meter	
<u>≤</u> 2	13,370
3 to 6	43,960
≥ 8	74,550
Ticket printer	3,310
Temperature	3,700
Brine Meters	
\leq 2 Low (pressure)	2,870
2 High (pressure)	4,200
3 Low (pressure)	4,700
3 High (pressure)	5,090
Digital Meter	
1	6,850
2 w/cubic meter readout	9,330



Subject: Meters

Section:

Turbine Meters and Totalizer

The rates for turbine meters and totalizers are in dollars per unit.

Size (in.)		Rate	
<u><</u> 2		12,640	
3		13,910	
Rates include:			
- meter	- 3	fittings	
- pipes	- 3	miscellaneous valves	
- totalizer	- :	installation	

Vortex Liquid Gas or Steam Meters

The rates for vortex liquid gas or steam meters are in dollars per unit.

Size (in.)		Rate	
2		5,710	
6		9,790	
8		15,550	
Rates include:			
- meter	-	- analog amplifier or enhancer	
- meter run	-	miscellaneous valves	
- fittings	-	installation	

Transmitters

The rates for transmitters are in dollars per unit.

Туре	Rate
Pressure or flow transmitter	9,790
Temperature transmitter	5,870

Additives

Туре	Rate per Readout
Computer Assist	1,180



Resource Production Equipment Subject: Meters

Weighmatic

The rate for weighmatic is in dollars per unit.

Description	Rate
Weighmatic - crude oil production rate test system Complete unit	126,980
Rates include:	
- separator	
- valves and fittings	
 computer related equipment 	
- installation	
Rates do not include gas metering equipment.	

Cabinet Type Meter Housing

The rate for a meter cabinet is in dollars per unit.

Туре	Rate	
Meter Cabinet	19,110	
Includes:		
- 1-2 pen dry flo	ow recorder	
- 2 door shed		
 small separate 	or and associated	
equipment		
- lines, values, meters, gauges, etc		
- installation		
- freight		



Subject:

Description

A valve is a device used to control the rate of flow in a line, to open or shut off a line completely, or to serve as an automatic or semi-automatic safety device.

Valves

The rates for valves are in dollars per unit.

Gate Valves

Size (in)	Rate	
Size (III.)	1500 Working Pressure (lb.)	
2	9,110	
3	12,240	
4	14,920	

Ball Valves

	Rate	
Size (in.)	Working Pressure (lb.)	
	< 2000	<u>> 2000</u>
2	4,810	5,960
3	6,350	7,740
4	8,190	11,940
6	11,590	16,230
8	21,050	30,220

Water Check Valves

	Rate					
Size (in.)	Working Pressure (lb.)					
	150 300 600					
< 4	1,550	1,910	2,230			
6 - 8	2,750	3,770	5,650			
10	5,130	6,590	9,840			
12	6,960	8,170	12,190			

Check Valves

Size	Rate
< 4	2,460
6	8,320
8	14,100



Resource Production Equipment

Subject: Valves and Controls

Desurgers

Size (in.)	Rate
<u><</u> 2	8,000
3	10,850
4	13,370

Pneumatic and Electric

	Rate		
Size (III.)	2-Way	3-Way	
Pneumatic			
<u><</u> 2	6,260	9,390	
3	8,570	13,470	
4	11,190	16,080	
6	18,120		
Electric			
<u><</u> 2	9,060	9,680	
3	11,350	12,180	
Rates include:			
- valve			
- actuator			
- installation	1		
NOTE: High-low pressure shutdown, rate at \$1,920.			
Intermitter (time cycle control), rate at \$2,580.			

Surface Safety Valves

Туре	Typical Model	Rate
Salfectuating	Willis B-15 & B-20	11,110
Sen actuaring	Willis C-15	11,110
	Willis HYG 20 3000#	16,720
Hydr/Elect. actuating	Willis HYG 30 3000#	16,720
	Willis HYG 40 3000#	16,720
	Willis PG 20 3000#	25,210
Pneumatic actuating	Willis PG 30 3000#	25,210
	Willis PG 40 3000#	25,210
Rates include:		
- valve		
 actuator and fittings 		
- installation		

Pressure Control Switch

Туре	Rate
Presco, Murphy	1,250



Subject: Valves and Controls

Choke

The rates for chokes are in dollars per unit.

Туре	Size (in.)	Rate
Low pressure and low volume	<u><</u> 2	1,430
High pressure and high volume	3 - 6	12,120

Lease Automatic Custody Transfer Unit

The rates for lease automatic custody transfer units are in dollars per unit.

	Rate		
Size (in.)	150 & 300 ANSI	600 ANSI	
2	109,640	119,950	
3	131,390	143,790	
4	163,670	190,630	
6	218,040	262,610	
8	270,930	346,260	
Rates include:			
- meter	- pi	pe fittings	
- sampler	- B.	S&W monitor	
- valves	- sk	id	
- strainer	- in	stallation	
 pressure indicato 	or		
Rates do not include boo	oster and shipping pun	nps.	



Subject: Valves and Controls



Subject: Pumps

Description

A pump is used to increase the pressure on a fluid in order to move the fluid through a pipe.

Rates

The rates for pumps are in dollars per unit.

Centrifugal Pump

Inlet Size (in.)	Rate
1	4,410
2	5,180
3	5,840
4	6,230
5	7,290
6	8,660

Gear Pump

Inlet Size (in.)	Rate
2	4,530
3	5,660
4	9,800
6	10,830

Progressive Cavity

Inlet Size (in.)	Rate		
1	4,440		
2	6,390		
3	8,220		
4	12,490		
6	14,600		
8 19,310			
NOTE:			
1) Add for prime move	ers		
2) The rates above are	for 1 stage pumps.		
Increase rate by 12%	b per stage for 2 and 3		
stage pumps			
Rate include:			
- pump			
- base			
- valves and fittings			
- installation			



Resource Production Equipment

Subject: Pumps

Reciprocating (Plunger) Pumps

	Rate			
Input (hp)	Simplex	Duplex	Triplex	Quintuplex
3	28,120	36,660		
5	31,060	37,380		
10	39,490	41,200		
< 21			44,440	53,000
21 - 40			56,170	67,040
41 - 70			81,160	131,270
71 - 100			118,760	142,950
101 - 150			145,990	215,890
151 - 250			202,280	222,840
> 250			362,110	364,430
Rates include:				
- pump				
- base				
- prime mo	over			
- installatio	on			

Transformer and Injection Pumps

Size (hp)	Rate
10	89,730
20	94,790
30	99,960
50	110,010
100	135,340
250	211,690
500	338,530
750	465,430
1000	592,500
Rates include:	
- motor	
- thrust chamber	
- intake section	
- pump	
- shutdown switches	
- skid	
- installation	


Description

Chemical injectors are used to add chemicals to prevent freezing, plugging or corrosion or to assist in whatever process is being carried out in the treatment or other cycle.

Rates

The rates for chemical injectors are in dollars per unit.

Description	Size (hp)	Rate
Electric motor driven	<u><</u> 2	7,760
(add for tanks > 60 imp. gal.)	3 and 5	19,690
Multiple head proportioning pump		8,050
Air/gas driven		4,530
Alcohol drip (9 imp. gal. tank)		1,600



Subject: Chemical Injectors



Subject: Compressors

Description

Compressors are used to supply air pressure to operate valves, fire flood wells and to transport gas in a flow line.

Utility Air Compressors

The rates for utility air compressors are in dollars per unit.

Size		Data	
(hp)	(KW)	Kate	
1⁄2 - 1	0.37	8,060	
11⁄2 - 3	2.20	14,180	
5	3.70	17,130	
Rates include:			
- air receiver			
- motor			
- installation			

Instrument Air Compressors

The rates for instrument air compressors are in dollars per unit.

Size		Data	
(hp)	(KW)	Kate	
< 10	0.37	34,570	
11 - 15	7.46 - 11.19	47,590	
16 - 20		64,610	
> 20		70,100	
Rates include:			
- air receiver			
- explosion-p	proof motor		
- dryer and after cooler			
- installation			



Subject: Compressors

Section:

Injection Air Compressors

The rates for injection air compressors are in dollars per unit.

Size (hp)	Rate		
400	1,126,710		
550	1,443,450		
1000	2,299,510		
2000	2,606,360		
3000	3,097,200		
4000	3,653,320		
Rates include:			
- air intake, coolers	- valves		
 fittings and equipment 	- concrete base		
- engine or electric mote	or - installation		
 miscellaneous pipes 			
 metering and controls 			

Natural Gas Compressors

The rates for natural gas compressors are in dollars per horsepower unit.

Description	Rate
Turbine engine/centrifugal (gas plant)	8,020
Reciprocating engine (gas plants)	5,670
Reciprocating or electric (field gathering)	3,760
Rates include:	
- building	
- gauge board	
- filters	
 electrical equipment 	
 atmospheric-type jacket water cooler 	
- free air and exhaust duct	
- scrubber	
- supports	
- electrical substation	
 skid or concrete base 	
 suction or discharge bottles 	
- compressor	
 conductors and conduit 	
- central panel	
- pumps	
- intake or exhaust silencer	
- main switchboard	
- installation	



Description

Resource Production Equipment

Cathodic protection uses a rectifier with a network of wires and anodes installed to create an electric field around flow lines and casing in corrosion prevention.

Rates

The rates for cathodic protection rectifiers are in dollars per unit.

Size (amperage)	Rate
Single well (12 - 16)	13,780
Field system (17 - 25)	20,650
Rates include:	
- rectifier	
- conduit and fittings	
- 2" x 60" steel anodes	
 cadwelds and handicap 	
- cables	
 splice kits and connect 	tors
- installation	





Subject: Control Panels

Description

Control panels are switches and other devices used to start, stop, measure, monitor or signal the operation of equipment.

Rates

The rates for control panels are in dollars per unit.

Power Rating		Data	
(hp)	(KW)	Kate	
<u><</u> 50	< 38	30,970	
51 - 450	38 - 336	68,980	
451 - 850	337 - 634	120,270	
851 - 1500	635 - 1119	205,950	
1501 - 2500	1120 - 1865	275,610	
2501 - 4000	1866 - 2984	343,770	
Rates include:			
- relays			
- control circuit gauges			
- installation			



Subject: Control Panels



Subject: Steam Generators

Description

Steam generators are used to inject steam to the producing formation for enhanced oil recovery systems.

Rates

The rates for steam generators are in dollars per unit.

Description	Rate
10,000,000 BTU/hr. unit	
Generator	1,083,880
Water softener and filter	85,890
Trailer	120,200
Building (on trailer)	81,480
Total for Unit	1,371,450
18,500,000 BTU/hr. unit	
Generator	1,093,750
Water softener and filter	85,970
2 Trailers (soft and gen)	188,530
2 Buildings (on trailer)	140,450
Total for unit	1,508,700
22,000,000 BTU/hr. unit	
Generator	1,110,820
Water softener and filter	96,120
2 Trailers (soft and gen)	222,700
2 Buildings (on trailer)	147,400
Total for unit	1,577,040
25,000,000 BTU/hr. unit	
Generator	1,268,380
Water softener and filter	103,070
1 Trailers	188,520
1 Buildings	85,980
Total for unit	1,645,950
50,000,000 BTU/hr. unit schedule 80 to 160	
1,750 to 2,400 psi	
Base, installation, tie-in	2,350,440
Generator	2,400,000
Water softeners and filters	200,000
Materials and accessories	381,460
Total for Unit	5,331,900



Section: Oil & Gas Well Resource Production Equipment

Resource Production Equipment

Subject: Steam Generators

Description	Rate
≥ 100,000,000 BTU/hr. unit schedule 80 to 160	
1,750 to 2,400 psi	
Base, installation, tie-in	2,579,130
Generator	3,238,000
Water softeners and filters	275,000
Materials and accessories	381,460
Total for Unit	6,473,590
Rates include:	
- softeners	
- filters	
- accessories	
- installation	



Section:

Description

Filters are used for cleaning water.

Sand Filter

The rates for sand filters are in dollars per tank unit.

Tank Size (in.)	Imp. Gal. per Minute	Pipe Size (in.)	Rate
20 x 54	30	11/2	17,010
24 x 54	40	11/2	19,730
30 x 60	60	2	26,900
36 x 60	90	21/2	35,330
42 x 60	120	3	54,770
48 x 60	150	3	66,440
60 x 60	250	4	97,420
72 x 60	420	6	148,440
84 x 60	580	6	197,400

Carbon Filter

The rates for carbon filters are in dollars per tank unit.

Tank Size (in.)	Imp. Gal. per Minute	Pipe Size (in.)	Rate	
20 x 54	10	11/2	15,640	
24 x 54	15	11/2	18,470	
30 x 60	25	2	22,670	
36 x 60	35	2	30,350	
42 x 60	50	21/2	43,860	
48 x 60	65	21/2 52,040		
60 x 60	100	3 71,100		
Rates include:				
- conc	crete base	 miscellaneous pipes 		
- values and fittings		- installation		



t Subject: Filters



Subject: Industrial Water Softeners

Description

Water softeners are used to soften the water for steam generators.

Rates

The rates for industrial water softeners are in dollars per tank unit.

Single Unit

Softener Tenk	Softener TankBrine TankImp. Gal.idth (in.) x Height (in.)Width (in.) x Height (in.)per Minute	Jame Cal	Din a Cina	Rate	
Width (in.) x Height (in.)		(in.)	Single Units	Duplex Units	
20 x 54	24 x 80	55	2	24,060	48,160
24 x 54	30 x 48	75	21/2	28,280	56,600
30 x 60	38 x 48	125	3	38,530	77,060
36 x 60	42 x 48	175	4	51,110	102,280
48 x 60	48 x 60	150	3	59,130	118,170
54 x 60	54 x 60	275	4	69,540	139,040
60 x 60	60 x 60	400	4	78,790	157,620
72 x 60	72 x 60	560	6	120,760	241,500
84 x 60	84 x 60	760	6	160,740	321,570
Deter in 1 des					

Rates include:

- time clock control

- specific gravity meter

- injectors
- valves and fittings

- liquid level control

- hardness monitor

Rates do not include pumps and motors.

- concrete base
- water meters
- chemical
- miscellaneous pipes
- installation





Description

A flow line is a line of pipe used to transport or conduct oil or gas from a well site to a tank, battery, satellite, gas plant, compressor station, or other facility at which the oil or gas is prepared for pipeline transport.

A service line is a line of pipe used to transport water from a water source well, or to transport water, steam, air, oxygen, acid or carbon dioxide to enhance the recovery of oil from an oil well.

Oil, Gas, Water and Air Lines

Resource Production Equipment

The rates for oil, gas, water and air lines are in dollars per lineal foot.

Line Sine (in)	Rate				
Line Size (in.)	Plastic (L)	Steel (N)	Fibreglass (F)		
1	8.05	18.96			
2	9.45	20.86	19.01		
3	12.97	25.11	24.71		
4	17.05	28.85	33.15		
6	28.96	39.36	58.59		
8		53.29	91.69		
10		71.80	111.70		
12		87.06	136.69		
14		94.44	161.68		
Rates include:					
- construction contract					
- land right-of-	- land right-of-way				
- pipe	- pipe				
- exterior coating					
- damages and pre-staking					
- engineering					
- radiographic inspection					
- legal survey					

Internal Coated Pipes

The rates for internal coated pipes are in dollars per lineal foot.

Pipe Size (in.)	Rate (C)
2	49.67
3	61.50
4	74.90
6	110.73
8	146.50



Steel Pipe with Polyethylene Liner

The rates for steel pipe with polyethylene liner are in dollars per lineal foot.

Pipe Size (in.)	Rate
2	44.70
3	50.26
4	57.00
6	78.06
8	97.15
10	121.30
12	153.48
14	182.40

Steam Service Lines

The rates for steam service lines are in dollars per lineal foot.

Pipe Size (in.)	Rate
1	64.71
2	73.54
3	75.62
4	79.06
6	102.52
8	123.62



Subject: Manifolds

Description

Manifolds are above ground connections where flow lines can be tapped for measurement.

Rates

The rates for manifolds are in dollars per manifold.

Production

	Rate		
Size (in.)	Manual	Automatic	
1	2,950	10,260	
2	7,320	13,690	
3	10,550	20,300	
4	14,460	25,490	
6	20,890	32,280	

Injection

Size (in)	Rate			
Size (m.)	Water	Air & Gas	Steam	
2	8,620	9,350	11,110	
3	12,020	12,910	15,470	
4	15,670	16,700	19,980	
Rates include:				
- pipe				
- fittings				
- valves				
- installation				



ent Subject: Manifolds



9 1 1

Description

Scraper traps are used to insert scrapers to clean out the flow lines and service lines.

Rates

The rates for scraper traps are in dollars per trap or injection unit.

Receiving and Launching Traps

Lino Sizo (in)	Rate		
Line Size (iii.)	With Bypass	Without Bypass	
2	10,890	4,920	
3	13,160	6,030	
4	15,290	6,990	
6	22,650		
8	29,220		
10	41,920		
12	53,120		

Automatic Pig Injection

Line Size (in.)	Rate
2	15,130
3	24,500
4	40,150
Rates include:	

- valves

- miscellaneous pipe and fittings
- installation



Subject: Scraper Traps



Description

Resource Production Equipment

In heavy oil areas, oil is often trucked to the battery where it is measured by weight and dumped into a receiving pit.

Rates

Balance scales are the typical platform-type scale that allow the complete vehicle to be weighed. Load cell scales weigh one set of axles at a time. The rates for scales are in dollars per unit.

Туре	Rate
Balance scale	197,730
Load cell scale	150,200



Subject: Truck Scales



Sectio

Resource Production Equipment

Summary

This section describes the formulas, rules and principles for determining the assessed value of mine resource production equipment.

Definitions

Mine resource production equipment is the fixtures, machinery, tools, railroad spur tracks, and other appliances used to extract and produce the ore but does not include equipment used to process or refine the ore.

Shaft linings, safety equipment, shop tools for maintenance service, spare parts, and surplus equipment are not resource production equipment by which a mine is operated.

Formulas, Rules and Principles

The assessed value of mine resource production equipment shall be determined by the replacement cost method established in this section. The replacement cost new shall be determined using the unit-in-place method or the trended original cost method.

The replacement cost of continuous belt conveyors over 1,000 feet in length, and solution mining resource production equipment shall be determined by the unit-in-place method. The unit-in-place base rates account for all direct and indirect costs. No additional adjustments shall be made to the base rates.

The unit-in-place base rates for solution mining resource production equipment shall be determined in accordance with the rates schedules in Chapter 4 – Resource Production Equipment, Section 4.1 – Oil and Gas Well Resource Production Equipment.

The trended original cost shall include all direct and indirect costs. Direct costs include materials, labour, supervision, equipment rentals, and utilities. Indirect costs include architectural and engineering fees, building permits, title and legal fees, insurance, interest and fees on construction loans, taxes incurred during construction, advertising and sales expense, and overhead and profit. Trended original costs shall be determined FOB the mine site as of January 1, 2015.

Depreciation shall be determined by calculating the amount of physical deterioration using the lifetime depreciation method. Functional and economic obsolescence shall not be accounted for in the calculation of depreciation. No additional allowance shall be made for depreciation except as may be accounted for in the downtime allowance factor.

The downtime allowance and the downtime allowance factor for mine resource production equipment shall be determined by the schedule of rates method. The downtime allowance and the downtime allowance factor shall account for all the loss in value due to under-utilization of the resource production equipment. This includes any loss in value due to differences in replacement cost and difference in the amount of depreciation, that have not been taken into account using the procedures in this manual.





Resource Production Equipment Subject: General Rules

Replacement Cost New

The following mine resource production equipment shall be valued:

- Head frame and head house including mechanical and electrical equipment;
- Service and production hoists c/w cages, skips, pulleys, cables, guide ropes and rails, skip load and dump facilities;
- Water control pipes, pumps, motors;
- Compressed air service piping, compressors, motors, controls;
- Personnel and service vehicles;
- Mobile and overhead cranes, forklifts;
- Ventilation systems, fans, ducts;
- Heating and cooling facilities;
- Warning system;
- Production equipment miners, drag lines, loaders, loading shovels, front-end loaders, ore trucks, ore haulers, scoop trams, conveyor systems and numerous ancillary and auxiliary equipment;
- Drills and blasting equipment;
- Feeders and crushers;
- Roof and floor maintenance equipment, rock bolters, graders, scraper haulers;
- Crawler and wheel tractors c/w dozers and/or buckets;
- Electrical wiring and equipment required to operate plant and equipment; and
- Any other equipment used in the mining operation that is not listed as an exclusion.

The following mine resource production equipment shall not be valued:

- Shaft linings concrete, steel, wood, etc. (tubing and cribbing);
- Safety equipment fire, personal, etc.;
- Sharp tools for maintenance and service;
- Spare parts; and
- Surplus equipment.

Unit-In-Place Method

The replacement cost of new conveyors and solution mining resource production equipment shall be determined as follows:

- 1. Determine the type of resource production equipment using the rating guide.
- 2. Determine the features requiring unit-in-place adjustment.
- 3. Calculate the replacement cost of the resource production equipment by adjusting the base rate by the unit-in-place adjustments.



Resource Production Equipment Subject:

Trended Original Cost Method

The replacement cost new shall be determined as follows:

- 1. Determine the original construction cost of all the resource production equipment at the facility.
- 2. Determine the direct and indirect costs requiring an adjustment.
- 3. Determine the comparative cost index for mine resource production equipment required to adjust construction costs to January 1, 2015.

General Rules

- 4. Calculate the construction cost of all the resource production equipment at the facility by adjusting the original construction cost for any direct or indirect costs requiring adjustment and multiplying the adjusted original construction cost by the comparative cost index.
- 5. Determine replacement cost of conveyors and solution mining resource production equipment that is valued by the unit-in-place method.
- 6. Calculate the replacement cost new of the resource production equipment by subtracting the replacement cost new of conveyors and solution mining resource production equipment from the construction cost of all the resource production equipment in the facility.

Physical Deterioration

Lifetime Depreciation Method

The amount of physical deterioration shall be 40 percent. When calculating replacement cost less depreciation no additional allowance shall be made for depreciation.

Downtime Allowance

Schedule of Rates Method

The downtime allowance for all mine resource production equipment shall be 10 percent.

Downtime Allowance Factor

Schedule of Rates Method

The downtime allowance factor shall be determined for mine resources production equipment that is not used for 30 days or more in the 12 month period preceding January 1st of the year to which the assessment roll relates.

Periods of time less than 7 consecutive days during which mine resource production equipment is not used shall not be included in the calculation of the number of down days.

The downtime adjustment factor shall be determined by application of the following formula:

DAF = 1	<u>DD - 3</u> - 365	<u>0</u>	
where:	DAF	=	downtime adjustment factor
	DD	=	number of down days



Resource Production Equipment

Subject: General Rules

Calculation Procedure

Description	Document No.	Page No.
a) Conveyor Base Rate	4.2.3	1
b) Unit-in-Place Resource Production Equipment	4.2.1	2
c) Trended Original Cost Resource Production Equipment	4.2.1	3
d) Replacement Cost New = $(a + b + c)$		
e) RCN less Physical Deterioration and Downtime		
Allowance = $d x (1 - (e_1 + e_2))$		
e ₁ . Physical Deterioration	4.2.1	3
e ₂ . Downtime Allowance	4.2.1	3
f) Downtime Allowance Factor	4.2.1	3
g) Assessed Value (e x f)		



Section:

Resource Production Equipment

Mine Resource Production Equipment Subject: **Comparative Cost Factor**

Description

The comparative cost factors are used to determine the replacement cost new of mine resource production equipment valued by the trended original cost method.

Application

The trended original cost method shall be used when the individual components of resource production equipment cannot be determined or estimated. The trended original cost method shall not be used to determine the replacement cost of conveyors or solution mining resource production equipment.

Comparative Cost Factor

The comparative cost factor shall be used to calculate the replacement cost new of resource production equipment as of January 1, 2015.

Factors

Year	Comparative Cost Factor
1940 and older	
1941	
1942	
1943	
1944	
1945	
1946	
1947	
1948	
1949	
1950	
1951	
1952	
1953	
1954	
1955	
1956	
1957	
1958	
1959	
1960	
1961	
1962	
1963	
1964	
1965	
1966	
1967	
1968	
1969	
1970	
1971	
1972	
1973	
1974	

Portions of this section are not available for viewing due to licensing with Marshall and Swift. Therefore the factors etc. have been intentionally left blank.

This information is available for purchase by contacting:

Technical Standards and Policy Division Saskatchewan Assessment Management Agency 200 - 2201 - 11th Avenue Regina, Saskatchewan S4P 0J8

Phone: (306) 924-8000 Toll Free: 1-800-667-SAMA (7262) Fax: (306) 924-8070

Email: info.request@sama.sk.ca

Web Site: http://www.sama.sk.ca



Resource Production Equipment

Subject: Comparative Cost Factor

Year	Comparative Cost Factor
1975	
1976	
1977	
1978	
1979	
1980	
1981	
1982	
1983	
1984	
1985	
1986	
1987	
1988	
1989	
1990	
1991	
1992	
1993	
1994	
1995	
1996	
1997	
1998	
1999	
2000	
2001	
2002	
2003	
2004	
2005	
2006	
2007	
2008	
2009	
2010	
2011	
2012	
2013	
2014 and newer	

This table is a derivative work based on the "Marshall Valuation Service" which is copyrighted material of Marshall & Swift/Boeckh © 2014. Unauthorized reproduction is expressly prohibited.



Resource Production Equipment

Subject: Conveyors

Description

Conveyors are used to transport ore within a mine facility.

Application

The rate schedule shall be applied to continuous belt conveyors over 1,000 feet in length. Continuous belt conveyors less that 1,000 feet in length and all special design, tripper automatic loading and unloading, extensible, mobile bridge and bridge conveyors shall be valued by the trended original cost method.

Continuous Belt Conveyor

The rates for conveyors are in dollars per lineal foot.

Belt Width (in.)	Rate
24	214
30	252
36	294
42	317
48	395
54	444
60	475
72	565
Rates include:	
- belting	
- drives	
- structure	
- hardware	

